

LIVINGLITE



Marl's Livinglite external lighting system offers a stylish and attractive way to decorate and illuminate your chosen space.

With over a million possible colour variations and a user friendly remote control system, the possibilities for setting the right mood and atmosphere for your patio or walkway are nearly endless.

Livinglite's completely unique design, extremely low power consumption and simple installation process make this colour-changing external lighting system one of the most exclusive outdoor lighting products available today.

MARL

LIVINGLITE



Starter Kit Contents



700-410-22-60

STARTER KIT

Part Number	705-410-22-65
Starter Kit Standard Parts	2x In-Line Units, 1x End Unit, 2x 2m Cables, 1x 4m Cable, 1x Power Supply Unit, 1x Colour Changing Unit, 1x Colour Changing Unit Remote Control
Light Output	2.6 – 28.5 lux
Voltage Input	90-250Vac
System Voltage	24Vdc
Beam Angle	120°
IP Rating	IP67
Operating Temperature	-20°C – 40°C
Housing	Polycarbonate Resin. Cast Acrylic. Stainless Steel
Dimensions LxWxD (mm)	(3x) 295x295x30
Weight (kg)	(3x) 2.2
Life Expectancy	Up to 10 years when used for 12 hours per day
Colour	RGB
Cleaning (Chemical Attack/Pressure Washing)	The unit is not designed to be pressure washed. The unit should be cleaned by first removing any excess contamination with a soft, non-abrasive cloth, followed by cleaning with warm water and a mild detergent, again using a soft, non-abrasive cloth to wipe the surface.
Warranty	1 year



Accessories

The following Accessories can be added to enhance your Starter Kit. The Livinglite Starter Kit can power up to 6x LED Light Units from a single Power Supply Unit, and up to 8x when a Booster Unit is added. Accessories are optional at the customers discretion.

Product	Part Number
In-Line Unit	702-410-22-60-1
End Unit	702-410-22-61-1
2 Metre Connecting Cable	702-000-00-50-1
4 Metre Connecting Cable	702-000-00-51
230V Power Supply Unit	702-000-22-50-1
Colour Changing Unit & Remote Control	702-000-22-51-1
Booster Unit & Power Supply Unit	702-000-22-53

Dimensions

